

## Tonmind 15W IP Wall Speaker SIP-S11

1. Transfer loud and excellent sound.
2. IP 55 waterproof design for installation on exterior of building.
3. 48K OPUS Audio Codec enables excellent sound quality .
4. Compatible with VoIP, SIP devices (IPPBX, IP Phone) via SIP.
5. Compatible with IP Camera VMS via ONVIF.
6. Support Pre-recorded messages.
7. Support HPPT API for alarm in transmit.



### Specification:

#### Audio

Decoding OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz

#### Speaker

Max SPL 101dB

Frequency response 80Hz~20KHz

Frequency Range 500-2KHZ +-10dB  
400-12KHZ +-20dB

Harmonic Distortion 0.1@1kHz

Signal to Noise Ratio 91dB

#### Network

Security: Password protection, IP address filtering, Digest authentication, User access log, firewall

Network Protocol: SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP

Network Interface: 10/100 Base-TX, RJ45

Support for SIP protocol for intergration with VoIP systimes, intergrated with SIP/PBX.

VoIP: Support SIP features: secondary/backend SIP server, IPv4 (IPv6 futhur)

Support codecs: OPUS, G711U, G711A, GSM, MP3

#### Amplifier

Amplifier Description: Built-in 15W Amplifier

#### General

Operating Temperature -30°C — +60°C

Operating humility 5%-85%

Material ABS (IP55 water-proof)

Rate Power 15W

Power Supply PoE or 12V

Installation Wall Mounted

Dimensions 296 x 196 x 157 mm

Net Weight 2.4 KG

Languages English

Warranty 2 years

Package Includes Network Wall Speaker  
User Manual